



GMBY.EX3045
Liquefied-gas-type Extinguishers

[Page Bottom](#)

Liquefied-gas-type Extinguishers

[See General Information for Liquefied-gas-type Extinguishers](#)

FIRE-END & CROKER CORP
 7 WESTCHESTER PLAZA
 ELMSFORD, NY 10523 USA

EX3045

Charge Lb	Min Use Temp F	Rating	Marine Type
Halon 1211			
2.5	-40	5-B:C	Yes
Halon 2211			
1.25	-65	2-B:C	No
2.5	-65	5-B:C	Yes
5.0	-65	10-B:C	Yes
9.0	-65	1-A:10-B:C	Yes
13.0	-65	2-A:40-B:C	Yes
17.0	-65	4-A:80-B:C	Yes
20.0	-65	4-A:80-B:C	Yes
50.0	-65	10-A:120-B:C	No
150	-65	30-A240-B:C	No

Last Updated on 1992-12-30

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".