



HLUG.EX4110 Ball Valves, System Control

[Page Bottom](#)

Ball Valves, System Control

[See General Information for Ball Valves, System Control](#)

NIBCO INC

WORLD HEADQUARTERS
1516 MIDDLEBURY ST
PO BOX 1167
ELKHART, IN 46515 USA

EX4110

System control ball valve, Models KT-505W-4, -8, in sizes 1, 1-1/4, 1-1/2, 2 and 2-1/2 in. with female threaded-end connections and rated 300 psig.

System control ball valve, Models KG-505W-4, -8, in sizes 2 and 2-1/2 in. with grooved-end connections and rated 300 psig.

Valves marked with a -4 suffix do not incorporate internal supervisory tamper switches.

Valves marked with an -8 suffix are supplied with internal supervisory tamper switches intended for indoor/outdoor use.

[Last Updated](#) on 2010-06-28

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".