



HLXS.EX3184 Butterfly Valves

Page Bottom

Butterfly Valves

[See General Information for Butterfly Valves](#)

NIBCO INC
WORLD HEADQUARTERS
1516 MIDDLEBURY ST
PO BOX 1167
ELKHART, IN 46515 USA

EX3184

Model	Size, NPS	Body Type	Pressure Rating, psig (Bar)	Indicator Post	Supervisory Switch*
Butterfly valve					
LD-3510-4	2-12	Lugged Wafer	250	—	—
LD-3510-8	2-12	Lugged Wafer	250	—	I, O
LD-3510-C-8	2-1/2, 3, 4, 6, 8	Lugged Wafer	250	—	I, O
ELD-3510-4	2-12	Lugged Wafer	250	—	—
ELD-3510-8	2-12	Lugged Wafer	250	—	I, O
WD-3510-4	2-12	Nonlugged Wafer	250	—	—
WD-3510-8	2-12	Nonlugged Wafer	250	—	I, O
WD-3510-C-8	2-1/2, 3, 4, 6, 8	Nonlugged Wafer	250	—	I, O
EWD-3510-4	2-12	Nonlugged Wafer	250	—	—
EWD-3510-8	2-12	Nonlugged Wafer	250	—	I, O
GD-1765-4N	10	Groove	175	—	—
GD-1765-8N	10	Groove	175	—	I, O
GD-4765-4N	2-1/2 thru 8	Groove	300	—	—
GD-4765-4N	76.1mm, 165.1mm	Groove	300	—	—
GD-4765-8N	2-1/2 thru 8	Groove	300	—	I, O
GD-4765-C-8N	2-1/2, 3, 4, 6, 8	Groove	300	—	I, O
GD-4765-8N	76.1mm, 165.1mm	Groove	300	—	I, O
GD-6765-4N	2-1/2 thru 10	Groove	350	—	—
GD-6765-4N	76.1mm, 165.1mm	Groove	350	—	—
GD-6765-8N	2-1/2 thru 10	Groove	350	—	I, O
GD-6765-8N	76.1mm, 165.1mm	Groove	350	—	I, O
GDL-4765-4N	2-1/2, 3, 4, 6, 8	Groove	300	—	—
GDL-4765-4N	76.1mm, 165.1mm	Groove	300	—	—
GDL-4765-8N	2-1/2, 3, 4, 6, 8	Groove	300	—	I, O

GDL-4765-8N	76.1mm, 165.1mm	Groove	300	—	I, O
GDL-1765-4N	10	Groove	175	—	—
GDL-1765-8N	10	Groove	175	—	I, O
FGD-3765-4N	2-1/2, 3, 4, 6, 8	Flanged to Groove	250	—	—
FGD-3765-4N	76.1mm, 165.1mm	Flanged to Groove	250	—	—
FGD-3765-8N	2-1/2, 3, 4, 6, 8	Flanged to Groove	250	—	I, O
FGD-3765-8N	76.1mm, 165.1mm	Flanged to Groove	250	—	I, O
FGD -1765-4N	10	Flanged to Groove	175	—	—
FGD-1765-8N	10	Flanged to Groove	175	—	I, O
FD-3765-4N	2-1/2, 3, 4, 6, 8	Flanged	250	—	—
FD-3765-4N	76.1mm, 165.1mm	Flanged	250	—	—
FD-3765-8N	2-1/2, 3, 4, 6, 8	Flanged	250	—	I, O
FD-3765-8N	76.1mm, 165.1mm	Flanged	250	—	I, O
FD-1765-4N	10	Flanged	175	—	—
FD-1765-8N	10	Flanged	175	—	I, O

* I = Indoor installation; O = Outdoor installation

Models designated -8, or -8N, have factory installed supervisory tamper switches, which are intended for indoor or outdoor use.

Models designated -4N do not have a tamper switches.

Models designated with a "C" suffix indicate that the valves incorporate a normally closed gear operator.

The suffix GP or WP indicates that the valve incorporates the stem extension for underground or through the wall installation respectively.

Last Updated on 2012-01-03

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".