



VPLX.EX744 Valves, Alarm

[Page Bottom](#)

Valves, Alarm

[See General Information for Valves, Alarm](#)

RELIABLE AUTOMATIC SPRINKLER CO INC

EX744

1470 SMITH GROVE RD
LIBERTY, SC 29657 USA

Model E, 2-1/2, 3, 4, 6, 8 in. and 65 mm sizes for horizontal or vertical installation.

Model E in the 4, 6 and 8 in. sizes for use with Model E-3 compact trim, rated pressure of 175 psig, for horizontal or vertical installation only.

Model E-3 in the 4, 6 and 8 in. sizes for use with Model E-3 compact trim, rated pressure of 300 psig, for horizontal or vertical installation only.

Model C water motor gong; Model E-1 retarding chamber with a Model B 3/4 in. strainer.

Model E, 3, 4, 6 and 8 in. and Model E-3 in the 4, 6 and 8 in. sizes are also suitable for use with Listed rubber gasketed fittings.

[Last Updated](#) on 2006-03-04

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".