



VTSR.EX3002 Hose Valves

[Page Bottom](#)

Hose Valves

[See General Information for Hose Valves](#)

NIBCO INC

WORLD HEADQUARTERS
1516 MIDDLEBURY ST
PO BOX 1167
ELKHART, IN 46515 USA

EX3002

Angle type, Fig. T-331-HC 2-1/2-in. size - for maximum working pressure of 300 psig. Bronze shut-off valves with renewable discs for use on standpipe equipment.

Gate type Fig T-103-HC 2-1/2-in. size - for maximum working pressure of 175 psig. Bronze shut-off valves of the solid wedge gate, inside screw pattern for use on pump and standpipe equipment.

[Last Updated](#) on 1996-06-14

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".